HCPCS Code ⁸	K0899 Power Mobility Device not coded by DME PDAC
Model	BA140
Weight Capacity	400 lbs.
Maximum Speed ²	Up to 8 mph
Ground Clearance ³	1.57" at motor skid plate 2.68" at front bumper 4.45" at mid-deck
Turning Radius ³	53"
Dimensions ³	Length: 49.6" Width: 27.83"
Seat-to-Deck Height	18.11"
Front & Rear Tires	9" solid
Suspension	Full suspension
Range Per Charge ^{2,5}	20Ah Battery Pack: Up to 14.5 miles at 220 lbs. Up to 11.25 miles at 400 lbs. 40Ah Battery Pack: Up to 29 miles at 220 lbs. Up to 22.5 miles at 400 lbs.
Total Weight ⁶	183.4 lbs. with 20 Ah battery pack 197.8 lbs. with 40 Ah battery pack
Heaviest Piece	71 lbs. (front)
Standard Seating	Type: Stadium seat with slider Material: Black Vinyl Width: 18.31" Depth: 17.32" Weight: 34.8 lbs.
Drive System	Rear-wheel drive, sealed transaxle, 36-volt DC motor
Dual Braking System	Regenerative and electromechanical
Battery Requirements ⁴	Type: Lithium-ion battery pack Size: 20Ah or 40Ah
Battery Weight ⁷	20 Ah: 20.8 lbs. 40 Ah: 35.2 lbs.
Battery Charger	4 amp, off-board charger
Warranty	Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Battery: 3 years

- 1 Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.
- 2 Varies with user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, tire type and tire condition. This specification can be subject to a variance of +10%, -5%.
- 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 4 Lithium-ion, AGM, Gel-Ćell, or Hybrid Gel (Hybrid Gel is defined as Nano Silica Gel Electrolyte with High Quality Glass Mat Separators) type required.
- 5 Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 6 Includes standard seat.
- 7 Battery weight may vary based on manufacturer.
- 8 DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement. HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. Payer coding, coverage, and bundling guidelines may apply.











CAPACITY

TOP SPEED

SUSPENSION

FDA Class II Medical Device¹



BUILT FOR THE BOLD.

It's time to discover what's really out there. With impressive ground clearance, a top speed of 8 mph, and a lithium-ion battery pack which powers up to a 29-mile range, the Baja® Bandit is built for exploring the unknown and confidently tackling rugged terrain away from the beaten path.

FEATURES

- Maximum speed of up to 8 mph
- 4.5" ground clearance
- 400 lb. weight capacity
- Competitive 53" turning radius
- Infinite tiller adjustment lever
- USB port for charging your devices
- Full LED lighting package for maximum visibility
- Full bumper package (standard)
- Supplemental hand brake for additional stopping power
- Feather-touch disassembly with the heaviest piece (front) weighing 71 lbs.
- Seat post with full suspension
- The upgradable dual lithium-ion battery configuration will deliver up to a 29-mile range on a single charge (14.5 miles with the standard single lithium-ion battery)
- 3-year warranty on lithium-ion battery

COLORS



Camo

Sage

Tan

ACCESSORIES

Only one rear accessory can be used at a time.

 3" single or double cane or crutch holder

Black

- 50/60/70" lap belt
- Cup holder
- Cell phone holder
- Forearm crutch holder
- Military patches
- Oxygen holder

- Quad cane holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Walker holder
- Weather cover
- Wishbone crutch holder

Cup holder, rear basket and saddlebag can be ordered as a bundle.